

# ROBBINS®

PHOTO: Craft Brown, Oak, EKHG75L06W

## HydroGuard™

WATERPROOF HARDWOOD

### Real Wood...for Real Life.

#### 100% real hardwood that is 100% waterproof

##### WATERPROOF

- Innovative 3-part system protects against water damage
  1. Tight locking system
  2. Proprietary coating on plank edges seals out water
  3. Hyper-dense core
- Top down moisture protection for up to 36 hours

##### DESIGN RANGE

- Wide variety of colors and textures
- Matte, low gloss finish

##### DURABLE

- Hardwood resists indentation; Janka hardness 2400-2500
- Resists scratches, stains and indentations for a lifetime of beauty

##### VERSATILE

- Kitchens, bathrooms and basements are no problem
- Install in any room and on any level

##### FAST / EASY INSTALL

- Flat/Balanced structure
- Robust locking profile
- No acclimation needed
- Attached IXPE pad for easy installation and sound absorption



100% Waterproof



Pet friendly



Resists scratches,  
stains and indentations



Install in any  
room and level

# ROBBINS®

## HydroGuard™ WATERPROOF HARDWOOD



Oak - Heavenly  
6-1/2" EKHG75L01S



Maple - Natural  
6-1/2" EMHG75L03S



Oak - Natural  
6-1/2" EKHG75L03H




Oak - Craft Brown  
6-1/2" EKHG75L06W




Hickory - Sugar Shack  
6-1/2" EHHG75L8BW




Hickory - Forest Beyond  
6-1/2" EHHG75L12W



Oak - Shaded Terrace  
6-1/2" EKHG75L09H




Oak - Iconic Brown  
6-1/2" EKHG75L00H



Oak - Good Earth  
6-1/2" EKHG75L21H



Oak - Summer Festival  
6-1/2" EOHG75L16W



Hickory - Twilight  
6-1/2" EHHG75L17W



Hickory - Deep Mountain  
6-1/2" EHHG75L15W

### HYDROGUARD ENGINEERED

<b>SPECIES</b>	Oak, Hickory, Maple	<b>THICKNESS</b>	1/2" Nom. + Pad	<b>FACE VENEER</b>	1.2 mm / Sliced**	<b>PAD ATTACHED</b>	1.5 mm
<b>TEXTURES</b>	Wire-Brushed, Hand-Scraped, Smooth Open Pore			<b>FINISH</b>	Nano Aluminum Oxide		
<b>WIDTH</b>	6-1/2"	<b>GLOSS</b>	Low	<b>LENGTH</b>	48" max; 4 fixed lengths, 16" min		
<b>EDGE DETAIL</b>	Micro-beveled edges and ends			<b>WARRANTY</b>	50-Year Limited Residential and 15-Year Limited Commercial		
<b>INSTALLATION</b>	Float, Glue	Below / On / Above Ground Level		<b>SQ FT PER PALLET</b>	852.40	<b>PALLETS PER TRUCK/CONTAINER</b>	25
<b>CARTONS PER PALLET</b>	40	<b>SQ FT PER CARTON</b>	21.31				

### HYDROGUARD SOUND TESTING

<b>IIC 67</b> 6" concrete with ceiling assembly	<b>IIC 53</b> 6" concrete NO ceiling assembly
<b>STC 63</b> 6" concrete with ceiling assembly	<b>STC 50</b> 6" concrete NO ceiling assembly
<b>Delta ΔIIC 23</b> 6" concrete NO ceiling assembly	



\*Janka Hardness Industry Standards: Oak 1290, Maple 1395, Hickory 1820. \*\*Maple not included.

WR-1107-1220 FloorScore is a trademark of the Resilient Floor Covering Institute. All other trademarks owned by AHF, LLC. © 2020 AHF, LLC.

NOTE: Due to printing limitations, colors pictured cannot be guaranteed to match actual flooring material.



TESTED BY  
ICC Global Services